



Acrylic Distemper (Pouch)

PRODUCT DESCRIPTION

Indigo Acrylic Distemper available in pouch packing is an entry level distemper available in bright colours.



PERFORMANCE FEATURES & BENEFITS

- Economical
- Bright Shades

FINISH

MATT

GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Plastered Walls

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



70% by Volume

SURFACE DRYING TIME



Surface Dry in 20 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



Clean and remove loose plaster or dust using sand paper.

SURFACE PREPARATION



NA

APPLICATION



Apply two coats of Indigo Acrylic (Pouch) Distemper on walls.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1st Coat: 10 - 11 sqm/kg* 2nd Coat: 6 - 7 sqm/kg*
Drying Time	3-4 Hrs
Sheen level	2.0 at 60 deg
Flash point	NA
Stability of thinned paint	NA
Appearance	Semi Solid
Solids	70
Specific gravity	1.73
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	400 by psi Penetrometer
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	97.5

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

Do not apply when the ambient temperature below 10°C. Do not apply directly on Lime wash or White cement painted wall

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



1 kg

SHADE RANGE

As per Shade Card



INDIGO
Be surprised!