



Exterior Emulsion

PRODUCT DESCRIPTION

Indigo Exterior Emulsion is a water based emulsion that provides protection for shaded exteriors. It has been designed to provide better hiding & coverage and a smooth matt finish.



PERFORMANCE FEATURES & BENEFITS

- Excellent resistance to chalking, cracking & weathering
- Clean & non-fading shades
- Anti-algae finish

FINISH

MATT

GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA

INTERIOR

EXTERIOR

SURFACES

Masonry - Concrete, Plastered walls etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well & strain before use

TOOLS



Brush, Roller & Spray

THINNING



Water

THINNING RATIO



65-75% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 degree celcius. Humidity below 70%

CLEANING



Clean the surface of loose paint, dust, grease etc. Use a wire brush and high pressure wash to remove all contaminants and algae growth, especially on horizontal areas, sunshades and such areas prone to water stagnation. Allow to dry.

SURFACE PREPARATION



For newly plastered surfaces allow 3-4 weeks curing time prior to painting. Leaks & cracks, if any, should be fixed before painting. Apply 2 coats of Indigo Polymer Putty & allow to dry. Apply 1 coat of Indigo Exterior Wall Primer & allow to dry.

APPLICATION



Apply 2 coats of Indigo Exterior Emulsion, obtained by thinning 1L of emulsion with 650-700ml of water. Allow 4-6 hours of drying time between coats. 3 coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 10-12 sqm/L*
	2 Coats: 6-7 sqm/L*
Drying Time	4-6 hours
Sheen level	2.2 @ 60 degree
Flash point	NA
Stability of thinned paint	24 hours
Appearance	Smooth white liquid
Solids	61%
Specific gravity	1.3 - 1.45
Recommended DFT	NA
Viscosity	2100CP @ 30°C by stormer viscometer
Shelf life	36 months
Contrast ratio	98%

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Wall should be free from moisture & new plaster should be allowed to cure for 4 weeks.
2. Leaks & cracks should be corrected before painting.
3. Ensure all traces of algae & fungi are removed before painting.
4. Horizontal areas like ledges, sunshades will require an additional coat for best protection.
5. Paint should only be applied on a dry surface and never during rain.

POST APPLICATION INSTRUCTIONS

For best performance, clean the walls to remove any accumulated dirt, dust & grease at regular intervals of 6 months. The dirt & grime work as an anchor and aids the growth of algae & fungi.

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Shade Card & Indigo Colour Fandek

