

Exterior Wall Primer

PRODUCT DESCRIPTION

Indigo Exterior Wall Primer is a water-based coating suitable for application on exterior walls as an undercoat to exterior emulsions.



PERFORMANCE FEATURES & BENEFITS

- Excellent opacity & whiteness
- Good resistance to chalking

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Masonry - Concrete, Plastered walls etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well & strain before use.

TOOLS



Brush, Roller & Spray

THINNING



Water

THINNING RATIO



85 - 90% by vol.

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty

APPLICATION ENVIRONMENT



Temperature:
10-40 degree celcius.
Humidity below 70%

CLEANING



Clean the surface of loose paint, dust, grease etc. Use a wire brush and high pressure wash to remove all contaminants and algae growth, especially on horizontal areas, sunshades and such areas prone to water stagnation. Allow to dry.

SURFACE PREPARATION



For newly plastered surfaces allow 3-4 weeks curing time prior to painting. Leaks & cracks, if any, should be fixed before painting. Apply 2 coats of Indigo Polymer Putty & allow to dry.

APPLICATION



Apply 1 coat of Indigo Exterior Wall Primer obtained by thinning 1L of paint with 850-900ml of water. Allow to dry for 4-6 hours.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

Spray application: Air-assisted spray application at pressure 25 - 30 psi

* Recoat period is quoted for 25° C and 50% Relative Humidity; these may vary under different conditions.

TECHNICAL DATA

Coverage	1 Coat: 10-12 sqm/L*
Drying Time	4-6 hours
Sheen level	NA
Flash point	NA
Stability of thinned paint	24 hours
Appearance	Smooth white liquid
Solids	52%
Specific gravity	1.4
Recommended DFT	NA
Viscosity	2345CP @ 30°C by stormer viscometer
Shelf life	36 months
Contrast ratio	95%

PRECAUTIONS

1. Wall should be free from moisture & new plaster should be allowed to cure for 4 weeks.
2. Leaks & cracks should be corrected before painting.
3. Ensure all traces of algae & fungi are removed before painting.
4. Overcoat primer using appropriate topcoat. Do not leave the primer exposed to sunlight & rainfall.
5. Paint should only be applied on a dry surface and never during rain.

POST APPLICATION INSTRUCTIONS

Apply Indigo Paints Exterior Emulsion over the primer within 7 days.

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

White

