

## Acrylic Wall Putty

### PRODUCT DESCRIPTION

Indigo Paints Acrylic Wall Putty is a water based putty for interior. It provides a durable foundation and brings out the best performance from the finish paint both in looks and durability.



### PERFORMANCE FEATURES & BENEFITS

1. Good filling Properties
2. Smooth Finish
3. Quick drying

#### FINISH

**MATT**

GLOSS

#### WASHABILITY

**NO**

LOW

MEDIUM

HIGH

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

Cement plasters, Asbestos sheets, Concrete etc

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Stir well before use

#### TOOLS



Putty blade

#### THINNING



NA

#### THINNING RATIO



NA

#### SURFACE DRYING TIME



Surface Dry in 30 Min.

#### FILLING



NA

#### APPLICATION ENVIRONMENT



Temperature:  
10-40 Degree  
Humidity: Below 80%

#### CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

#### SURFACE PREPARATION



Allow 3 months curing prior to painting for newly plastered surfaces. Apply Indigo Cement Primer. Allow to dry.

#### APPLICATION



Fill the dents in the surface with Indigo Acrylic Wall Putty. Repeat sanding with abrasive paper, and apply more coats if more smoother surface is required giving drying time and sanding between each coat. Wipe clean, and apply another coat of Indigo Cement Primer.

#### SAFETY FEATURES



Non- flammable  
No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

<b>Coverage</b>	1st Coat: 3- 4 sqm/kg* 2nd Coat: 2 - 3 sqm/kg*
<b>Drying Time</b>	4-6 hours
<b>Sheen level</b>	2.3 @60
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24Hrs
<b>Appearance</b>	Semi Solid
<b>Solids</b>	73.5
<b>Specific gravity</b>	NA
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by stormer Viscometer</b>	340 on DOP
<b>Pot life</b>	24Hrs
<b>Shelf life</b>	24 Months
<b>Contrast ratio</b>	NA

\*\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

## PRECAUTIONS

1. Do Not Over Thin, 2. Do not apply when temp is below 10°C or if temp might drop withn 4 hrs of painting

## POST APPLICATION INSTRUCTIONS

NA

## AVAILABLE PACK SIZE

Available in:



## SHADE RANGE

White

