



Indigo Roof Paint

PRODUCT DESCRIPTION

Indigo Roofing enamel is a superior synthetic enamel specially formulated with high water resistant alkyds and additives for use in hilly areas and high rainfall zones. It is mainly designed to be used on roofs made from corrugated metal sheets and can also be applied on beams, angles, joints, asbestos roof, MS grills, gates etc.



PERFORMANCE FEATURES & BENEFITS

- High water resistance
- Good Gloss
- Anti Corrosive finish

FINISH

MATT

GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Wood, metal & asbestos after appropriate priming

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well before use.

TOOLS



Brush, Spray

THINNING



Good quality turpentine

THINNING RATIO



10-15%

SURFACE DRYING TIME



Surface Dry in 60 mins.

FILLING



Depending on the substrate use appropriate fillers.

APPLICATION ENVIRONMENT



Temperature
10-40 Degree Celcius
Humidity: Below 80%

CLEANING



Clean the surface of loose paint, dust and grease. Wipe clean using turpentine and allow to dry.

SURFACE PREPARATION



Sand the surface with abrasive paper grit no. 180. Wipe clean and use appropriate primer like Zinc Chrome primer for Metal surfaces / Wood Primer for wooden substrates / Cement primer for Asbestos surfaces. Dents and imperfections can be filled using the appropriate fillers which should then be sanded and primed again.

APPLICATION



Apply 2 coats of indigo Roof Paint by brush or spray. Allow to dry for 6-8 hours between coats.

SAFETY FEATURES

No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat - 9 - 10 sqm/L 2 Coats - 6 - 7 sqm/L
Drying Time	6 - 8 hours
Sheen level	80 @60 degree
Flash point	above 30 degree
Stability of thinned paint	NA
Appearance	Liquid
Solids	NA
Specific gravity	NA
Recommended DFT	NA
Viscosity	80sec @ 30°C by Ford Cup.
Shelf life	36 months
Contrast ratio	NA

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

Ensure appropriate primers are applied depending on the surface being painted.

POST APPLICATION INSTRUCTIONS

AVAILABLE PACK SIZE

Available in:



1L



4L



20 L

SHADE RANGE

Green, Blue, Red



INDIGO
Be surprised!