



Luxury Interior Emulsion

PRODUCT DESCRIPTION

Indigo Luxury Interior Emulsion is a high opacity Interior wall finish with soft sheen. It is based on pure acrylic emulsion with exceptional flexibility and easy cleaning properties to remove tough stains.



PERFORMANCE FEATURES & BENEFITS

1. Rich Smooth Finish
2. Superior Washability
3. High stain resistance
4. Low odour
5. Fungus & mildew resistant

FINISH

MATT

SHEEN

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Cement plasters, Asbestos sheets, Concrete, Brickwork, etc

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller & Spray

THINNING



Water

THINNING RATIO

Brush Application:
40 % by Volume
Roller Application:
10-15% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature:
10-40 Degree
Humidity: Below 80%

CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

SURFACE PREPARATION



Allow 3 months curing prior to painting for newly plastered surfaces. Apply Indigo Cement Primer. After drying for 8 hours, fill the dents in the surface with Indigo Polymer Putty. Apply another coat of Indigo Cement primer. Allow to dry.

APPLICATION



Apply 2-3 coats of Indigo Luxury Interior Emulsion, obtained by thinning 1 L of emulsion with 400 ml of water by brush or 150ml water by roller. Allow 4-6 hours drying time between each coat.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

Spray application: Air-assisted spray application at pressure 25 - 30 psi

* Recoat period is quoted for 25° C and 50% Relative Humidity; these may vary under different conditions.

TECHNICAL DATA

| | |
|--|---|
| Coverage | 1st Coat: 24- 26 sqm/L* 2nd Coat: 12 - 13 sqm/L* |
| Drying Time | 4-6 hours |
| Sheen level | 8-12 @60 |
| Flash point | NA |
| Stability of thinned paint | 24Hrs |
| Appearance | Liquid |
| Solids | 56.5 |
| Specific gravity | 1.32 |
| Recommended DFT | NA |
| Viscosity @25°C by stormer Viscometer | 3100CPS |
| Pot life | NA |
| Shelf life | 24 Months |
| Contrast ratio | NA |

***Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

In case masking tape is being used to separate two areas while painting, it is recommended to remove all masking tape before the paint film dries completely.

POST APPLICATION INSTRUCTIONS

To remove dirt/ stains, Clean the painted surface by sponging with a mild soap solution. Allow the paint to dry for 2 weeks before cleaning

AVAILABLE PACK SIZE

Available in:

**SHADE RANGE**

As per Indigo Colour fan deck

