

Premium Interior Emulsion

PRODUCT DESCRIPTION

Indigo Premium Interior Emulsion is a luxury emulsion for interior walls with matt finish. It provides high washability with resistance to fungal growth and black spots on interior walls.



PERFORMANCE FEATURES & BENEFITS



Easy to clean



Stain Resistance



Anti-fungal & Anti-Mildew

- High brightness
- Excellent hiding capacity"

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Concrete, Brick & Other Mansory Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



35-40% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

SURFACE PREPARATION



Apply Indigo Cement Primer. After drying for 8 hours, fill the dents in the surface with Polymer Putty. Repeat sanding with emery paper, wipe clean, and apply another coat of Indigo Cement Primer. After drying for 8 hours, sand with fine emery paper & wipe clean.

APPLICATION



Apply 2-3 coats of Indigo Premium Interior Emulsion, obtained by thinning 1 L of emulsion with 350-450 ml of water.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1st Coat: 18- 21 sqm/L* 2 Coat: 13 - 16 sqm/L*
Drying Time	4-5 Hrs
Sheen level	2.4 at 60 degree
Flash point	NA
Stability of thinned paint	24 Hrs
Appearance	Smooth, Liquid, Milky White
Solids	54 %
Specific gravity	1.39
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2200cp
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	98.79

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Wall should be free from moisture
2. If any wall is under seepage, treat it with proper waterproofing
3. Do not apply on any lime washed surfaces
4. In case of fungi or algae use Indigo Bio Clean to clean the surface

POST APPLICATION INSTRUCTIONS

"For cleaning stains use only soap water with white cotton cloth.
Attempt cleaning after a month of application of paint"

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Indigo Colour Fandek



INDIGO
Be surprised!