



Sleek NC Sanding Sealer

PRODUCT DESCRIPTION

Sleek NC Sanding Sealer is a high viscosity quick drying clear cellulose sealer for interiors which helps fill grains inherent to wood. It can be topcoated using single pack PU & melamine systems.



PERFORMANCE FEATURES & BENEFITS

- Quick drying
- Better clarity

FINISH

MATT

GLOSS

SILK MATT

MIXING RATIO

NA

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

It can be used on all types of interior wooden substrates like doors, windows, furniture, kitchen cabinets etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush, Spray, Rag cloth

THINNING



1 to 2 L of NC thinner depending on consistency

THINNING RATIO

1 L NC Sealer :
1 L NC Thinner

SURFACE DRYING TIME



10 minutes at 30°C

FILLING



NA

APPLICATION ENVIRONMENT



Temperature:
10-40 Degree
Humidity: Below 80%

CLEANING



Ensure that the wood is seasoned and the surface is well-dried.

- To remove the oiliness inherent to tannin rich wood such as teak and rose wood, wipe clean with NC thinner.

SURFACE PREPARATION



- Sand the wooden substrate along the grains, sequentially, with abrasive paper from grit numbers 80 to 180.
- The dust, dirt that comes out during the sanding process should be totally removed.

APPLICATION



Apply 2-3 coats of Sleek NC Sanding Sealer or till the pores in the wood are filled satisfactorily. Allow 2 hours drying time between coats and sand down using abrasive paper grit no.220. Wipe clean. Overcoat using appropriate topcoat.

SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	7 - 14 sqm/L/Coat*
Drying Time	2 hours
Sheen level	Matt
Flash point	Above 23°C.
Stability of thinned paint	-
Appearance	Off White
Solids	30+/-1%
Specific gravity	1
Recommended DFT	-
Viscosity @25°C by Stormer Viscometer	-
Pot life	NA
Shelf life	36 months
Contrast ratio	NA

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as type of substrate.

PRECAUTIONS

- Flammable
- Keep away from heat, sparks etc.
- Use appropriate protection during application.
- Ensure adequate ventilation during application.

POST APPLICATION INSTRUCTIONS

-

AVAILABLE PACK SIZE

Available in:



500 ml



1 L



4 L



20 L

SHADE RANGE

NA



INDIGO

Be surprised!