

## Sleek XT Exterior Single Pack PU

### PRODUCT DESCRIPTION

Sleek XT single pack PU Topcoat is a top quality product for the protection of all types of exterior wood work. Based on a modified PU binder and fortified with UV absorbers, it offers medium term protection for all types of exterior joinery under normal exposure conditions.

### PERFORMANCE FEATURES & BENEFITS

- Fortified with UV Filters
- Repels Water
- Easy to use



### FINISH

MATT

GLOSS

SILK MATT

### MIXING RATIO

NA

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

It can be used  
on all types of exterior joinery  
(like doors, windows) furniture etc.

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Stir well before use

#### TOOLS



Brush, Spray

#### THINNING



Turpentine

#### THINNING RATIO

10-20% by volume

#### SURFACE DRYING TIME



30 minutes

#### FILLING



NA

#### APPLICATION ENVIRONMENT



Temperature:  
10-40 Degree  
Humidity: Below 80%

#### CLEANING



Ensure that the wood is seasoned and the surface is well-dried.

- To remove the oiliness inherent to tannin rich wood such as teak and rose wood, wipe clean with NC thinner.

#### SURFACE PREPARATION



- Sand the wooden substrate along the grains, sequentially, with abrasive paper from grit numbers 80 to 180.
- The dust, dirt that comes out during the sanding process should be totally removed.

#### APPLICATION



Apply 2 coats of Sleek XT single pack PU topcoat by brush / spray with 6-8 hours drying time between coats. Inter-coat sanding using abrasive paper grit no. 320.

#### SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

|                                       |   |
|---------------------------------------|---|
| Coverage                              | 6 - 7 sqm/L/Coat*                                     |
| Drying Time                           | 6-8 hours   |
| Sheen level                           | 90-95° - Glossy<br>25-30° - SilkMatt<br>10-15° - Matt |
| Flash point                           | Above 34°C.   |
| Stability of thinned paint            | NA  |
| Appearance                            | Clear   |
| Solids                                | 46+/-1%   |
| Specific gravity                      | 0.92  |
| Recommended DFT                       | 25 to 30 microns per coat                             |
| Viscosity @25°C by Stormer Viscometer | -   |
| Pot life                              | NA  |
| Shelf life                            | 36 months   |
| Contrast ratio                        | NA  |

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as type of substrate.

## PRECAUTIONS

- Flammable
- Keep away from heat, sparks etc.
- Use appropriate protection during application.
- Ensure adequate ventilation during application.

## POST APPLICATION INSTRUCTIONS

For best performance, ensure periodic cleaning of the coated surfaces, at least once in 6 months, to remove accumulated dirt and grime that can lead to accelerated deterioration.

## AVAILABLE PACK SIZE

Available in:



500 ml



1 L



4 L

## SHADE RANGE

NA



**INDIGO**

Be surprised!