



## Sleek XT Exterior Single Pack PU

### PRODUCT DESCRIPTION

Sleek XT single pack PU Topcoat is a top quality product for the protection of all types of exterior wood work. Based on a modified PU binder and fortified with UV absorbers, it offers medium term protection for all types of exterior joinery under normal exposure conditions.



### PERFORMANCE FEATURES & BENEFITS

- Fortified with UV Filters
- Repels Water
- Easy to use

#### FINISH

MATT    GLOSS    SILK MATT

#### MIXING RATIO

NA

### RECOMMENDED USES

#### AREA

INTERIOR

EXTERIOR

#### SURFACES

It can be used on all types of exterior joinery (like doors, windows) furniture etc.

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Stir well before use

#### TOOLS



Brush, Spray

#### THINNING



Turpentine

#### THINNING RATIO

10-20% by volume

#### SURFACE DRYING TIME



30 minutes

#### FILLING



NA

#### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 80%

#### CLEANING



Ensure that the wood is seasoned and the surface is well-dried.

- To remove the oiliness inherent to tannin rich wood such as teak and rose wood, wipe clean with NC thinner.

#### SURFACE PREPARATION



- Sand the wooden substrate along the grains, sequentially, with abrasive paper from grit numbers 80 to 180.
- The dust, dirt that comes out during the sanding process should be totally removed.

#### APPLICATION



Apply 2 coats of Sleek XT single pack PU topcoat by brush / spray with 6-8 hours drying time between coats. Inter-coat sanding using abrasive paper grit no. 320.

#### SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

|                                       |   |
|---------------------------------------|---|
| Coverage                              | 6 - 7 sqm/L/Coat                                      |
| Drying Time                           | 6-8 hours   |
| Sheen level                           | 90-95° - Glossy<br>25-30° - SilkMatt<br>10-15° - Matt |
| Flash point                           | Above 34°C.   |
| Stability of thinned paint            | NA  |
| Appearance                            | Clear   |
| Solids                                | 46+/-1%   |
| Specific gravity                      | 0.92  |
| Recommended DFT                       | 25 to 30 microns per coat                             |
| Viscosity @25°C by Stormer Viscometer | -   |
| Pot life                              | NA  |
| Shelf life                            | 12 months   |
| Contrast ratio                        | NA  |

*\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as type of substrate.*

## PRECAUTIONS

- Flammable
- Keep away from heat, sparks etc.
- Use appropriate protection during application.
- Ensure adequate ventilation during application.

## POST APPLICATION INSTRUCTIONS

-

## AVAILABLE PACK SIZE

Available in:



500 ml



1 L



4 L

## SHADE RANGE

NA



INDIGO

Be surprised!