

Stain Block Primer

PRODUCT DESCRIPTION

Indigo Stain Block Primer is a water based primer suitable for use on interior / exterior walls and ceilings. It is specially formulated to prevent the migration of stains through the finished paint film. It can easily hide the stains caused by water and solvent based inks, crayons, ball-point pens, coffee, grease, spices and cooking oils, water, nicotine and smoke.



PERFORMANCE FEATURES & BENEFITS

- Excellent Hiding of Stains
- Prevents migration of stains through paint film
- Seals Powdery Surfaces, Limewash & Distemper

FINISH

MATT

GLOSS

WASHABILITY

YES

NO

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Masonry - Concrete, Plastered walls etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well & strain before use.

TOOLS



Brush or Short Pile Roller only. Do not spray

THINNING



Water

THINNING RATIO



NA

SURFACE DRYING TIME



Surface Dry in 30 mins

FILLING



NA

APPLICATION ENVIRONMENT



Temperature: 10-40 degree celcius. Humidity below 70%

CLEANING



Clean the surface of loose paint, dust, grease etc. Use a wire brush and mild soap solution to clean existing stains if any to the extent possible. Allow to dry.

SURFACE PREPARATION



To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from efflorescence, dirt, grease or wax. Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then wipe clean.

APPLICATION



Stir thoroughly and apply 1 coat of Stain Block Primer to the stained surfaces without diluting with water and allow to dry for 8 hrs. Two coats are recommended for difficult stains. Allow to dry and follow with regular primer & topcoat.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 11 - 13 sqm/L*
Drying Time	6-8 Hrs
Sheen level	NA
Flash point	NA
Stability of thinned paint	24 hours
Appearance	Smooth white liquid
Solids	49%
Specific gravity	1.26
Recommended DFT	NA
Viscosity	1200CP @ 30°C by stormer viscometer
Shelf life	36 months
Contrast ratio	NA

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Do not spray
2. When blocking stains caused by water or damp, make sure the original cause of the problem has been rectified.
3. When Indigo Stain Block Primer is applied initially, it will draw the stain into itself and then seal it – this is not a defect

POST APPLICATION INSTRUCTIONS

1. Ensure that the primer has dried completely before applying the topcoat.
2. On tough stains a second coat of Stain block primer can be applied for better results.
3. It is recommended to apply WTCP Primer or Exterior Wall Primer on top of Stain Block Primer before applying the topcoat.

AVAILABLE PACK SIZE

Available in:



1 L

4 L

10 L

SHADE RANGE

White



INDIGO

Be surprised!