



Stone & Tile Topcoat

PRODUCT DESCRIPTION

Indigo Stone & tile topcoat is a single pack solvent borne clear acrylic top coat available in matt & glossy for all kind of natural stones to give them long lasting good looks. It can be also used for paver blocks/concrete floors subject to light traffic.



PERFORMANCE FEATURES & BENEFITS

1. Easily applied by Brush.
2. Resistant to Algae and stain
3. Excellent water and Alkali resistance
4. Tintable with universal machine colorants

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Natural stones, Brick works

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well before use

TOOLS



Brush

THINNING



Mineral Turpentine

THINNING RATIO



Not recommended.
Max. 10% by volume
if required.

SURFACE DRYING TIME



Surface dry in 30 mins
at 30°C

FILLING



NA

APPLICATION ENVIRONMENT



Temperature:
10-40 Degree
Humidity: Below 70%

CLEANING



Substrate must be free of dust, laitance, efflorescence, grease, foam release oils and similar contaminants. Clean the surface thoroughly using a stiff brush and wash down with soap & clean water to remove algae growth, if any. Allow to dry completely. Then Clean with MTO.

SURFACE PREPARATION



If surface is smooth, to ensure good adhesion, roughen / sand the surface using abrasive paper grit no. 180

APPLICATION



Apply 2 coats of Indigo Stone & Tile Topcoat with a time interval of 3-4 hours between the coats

SAFETY FEATURES



Flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 50 - 60 sqft/ltr* 2 Coat: 25 - 30 sqft/ltr*
Drying Time	3-4 Hrs
Sheen level	Glossy: > 60 units and Matt < 10 units on 600 glossometer
Flash point	35°C
Stability of thinned paint	-
Appearance	Liquid
Solids	-
Specific gravity	0.85
Recommended DFT	30 - 50 microns
Viscosity @25°C by Stormer Viscometer	Ready to use viscosity
Pot life	-
Shelf life	24 months
Contrast ratio	-

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

Flammable. Keep away from heat, sparks etc.
Adequate ventilation during application
Use appropriate protection during application

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

Can be tinted with Machine colourants

