



## Metallic Emulsion

### PRODUCT DESCRIPTION

Indigo Metallic Emulsion is a revolutionary Paint, suitable for exterior as well as Interior walls. It is based on a pure Acrylic formulation and it gives sparkling metallic texture to the walls.



### PERFORMANCE FEATURES & BENEFITS



High Sheen

Excellent glitter

#### FINISH

MATT

**SEMI GLOSSY**

#### WASHABILITY

NO

LOW

MEDIUM

**HIGH**

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

Wood / Metallic / Concrete

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Shake well before use

#### TOOLS



Brush & Roller

#### THINNING



Water

#### THINNING RATIO



25-35% by Volume

#### SURFACE DRYING TIME



Surface Dry in 30 Min.

#### FILLING



Indigo Polymer Putty or Acrylic Wall Putty

#### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 70%

#### CLEANING



For exterior surfaces, scrub with wire brush and clean the surface of loose paint, dust and grease. For interior surfaces, clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

#### SURFACE PREPARATION



NA

#### APPLICATION



Apply a priming coat of Indigo Water Thinnable Cement Primer. Follow with 2 coats of Metallic Emulsion, obtained by thinning 1 litre of paint with 250-300 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

#### SAFETY FEATURES



Non- flammable  
No added Lead, Mercury or Chromium compounds

**TECHNICAL DATA**

<b>Coverage</b>	1st Coat-100-110 sq.ft/ltr* 2nd Coat- 60-70 sq.ft/ltr *
<b>Drying Time</b>	4 - 5 Hours
<b>Sheen level</b>	39.9 at 60 degree
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24 Hrs
<b>Appearance</b>	Liquid
<b>Solids</b>	35
<b>Specific gravity</b>	1.1
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by Stormer Viscometer</b>	2279 cp
<b>Pot life</b>	24 hrs
<b>Shelf life</b>	24 months
<b>Contrast ratio</b>	89.81

*\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

**PRECAUTIONS**

Do not dilute with thinner

**POST APPLICATION INSTRUCTIONS**

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

**AVAILABLE PACK SIZE**

Available in:



**SHADE RANGE**

As per Shade Card

