



## Acrylic Distemper (Pouch)

### PRODUCT DESCRIPTION

Indigo Acrylic Distemper available in pouch packing is an entry level distemper available in bright colours.



### PERFORMANCE FEATURES & BENEFITS

- Economical
- Bright Shades

#### FINISH

**MATT**

GLOSSY

#### WASHABILITY

**NO**

LOW

MEDIUM

HIGH

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

Plastered Walls

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Shake well before use

#### TOOLS



Brush & Roller

#### THINNING



Water

#### THINNING RATIO



70% by Volume

#### SURFACE DRYING TIME



Surface Dry in 20 Min.

#### FILLING



Indigo Polymer Putty or Acrylic Wall Putty

#### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 70%

#### CLEANING



Clean and remove loose plaster or dust using sand paper.

#### SURFACE PREPARATION



NA

#### APPLICATION



Apply two coats of Indigo Acrylic (Pouch) Distemper on walls.

#### SAFETY FEATURES



Non-flammable  
No added Lead, Mercury or Chromium compounds

**TECHNICAL DATA**

<b>Coverage</b>	1st Coat: 10 - 11 sqm/kg* 2nd Coat: 6 - 7 sqm/kg*
<b>Drying Time</b>	3-4 Hrs
<b>Sheen level</b>	2.0 at 60 deg
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	NA
<b>Appearance</b>	Semi Solid
<b>Solids</b>	70
<b>Specific gravity</b>	1.73
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by Stormer Viscometer</b>	400 by psi Penetrometer
<b>Pot life</b>	24 hrs
<b>Shelf life</b>	24 months
<b>Contrast ratio</b>	97.5

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

**PRECAUTIONS**

Do not apply when the ambient temperature below 10°C. Do not apply directly on Lime wash or White cement painted wall

**POST APPLICATION INSTRUCTIONS**

NA

**AVAILABLE PACK SIZE**

Available in:



1 kg

**SHADE RANGE**

As per Shade Card

